

TOMCAT 125 SERIES



APPLICATION Alien Clearing | Garden Services | Tea Tree | Feed for Livestock | Firewood Waste

CHIPPER FEATURES

- 125mm capacity chipper
- Single in-feed roller
- Manual feed control
- Hydraulic tank
- Swivel discharge chute
- Forward/reverse bar
- Foldable feed tray
- Replaceable wear strips
- Hour meter
- Takbok hydraulics
- Sealed bearings
- Trailerised options available

125 mm Drum-Style Hydraulic-Feed Chippers

The smallest and most economic hydraulic-feed chipper in our range. Its simplicity makes it extremely easy to operate and maintain. A single hydraulic-powered in-feed roller helps to draw in those side branches which are too difficult for a gravity-feed unit to chip. This reduces prep time and increases production and efficiency. A forward/reverse bar is used to manually change the feed direction or control the feed rate when larger diameter branches are chipped. A 360° swivel discharge chute & chip deflector allow the operator to control the direction of the chip discharge. The chipper drum is belt-driven for added safety. The Model 125 is available in two models: 125 AFP PTO, which fits behind a tractor, or the 125 AFE, which is conveniently fitted on a roadworthy trailer and powered by its own petrol engine. A manual jack is included on both models to manually lift the slide-box during maintenance.

The engine driven unit is built on a lightweight but heavy-duty trailer. It comes with a spare wheel, a toolbox and automatic centrifugal clutch system. The tractor-powered unit comes with a PTO-shaft and the well-positioned connection points on the base allow for quick connection to the tractor.



*Price difference

E & OE **DESIGNED & MANUFACTURED IN SOUTH AFRICA**

www.tomcatchippers.co.za