

DEZZI

EST. 1973



3 WHEEL LOGGER

BUILT AFRICA TOUGH

3 WHEEL LOGGER



Engine

MAKE :	Deutz F4L912
POWER :	46KW / 230NM @ 1600RPM
RPM :	Governed @ 2000RPM
MOUNTING :	6 Point Rubber Mounting
SAFETY :	Mechanical Shut Off

Attachment

TIMBER / BRUSH GRAPPLE

- 0.36m³
- Indexator GV125A Heavy Duty

Drive Pump

MODEL :	Poclain - PM50 Tandem
OPERATOR CONTROL :	Servo Foot Pedal Valve
DISPLACEMENT :	45cc Per Side
RELIEF VALVE :	350 Bar
CHARGE PUMP :	Intergrated Gear Pump
CHARGE PRESSURE :	25 Bar
DRIVE COUPLING :	HD Guardex 65

Wheels

TYRES FRONT :	18.4 x 30" Logger
FRONT RIM :	15 x 30 Reinforced 1 piece
TYRE OPTION FRONT :	23.1 x 26 Forestry Special
RIM OPTION FRONT :	20 x 26 HD Reinforced
TYRES REAR :	400/60 x 15.5 High Floatation
REAR RIM :	13 x 15.5 Reinforced 1 piece

Brakes

TYPE :	Multi Disc Spring Applied
PARK BRAKE RELEASE :	18 Bar Hydraulic Pressure
SERVICE BRAKE :	Hydrostatic Foot Pedal Control

Hydraulic & Fuel Tank

HYDRAULIC TANK TYPE :	Frame Tubing Integrated
HYDRAULIC TANK CAPACITY :	145L (170 For System)
HYDRAULIC OIL COOLING :	Electric Fan Hydraulic Cooler
FUEL TANK TYPE :	Bolt Mounted on Frame
FUEL TANK CAPACITY :	85L

Implement Hydraulic System

PUMP TYPE :	Boom - 31 cc
	Implement Pump - 19cc
FUNCTION VALVE :	Open Centre Valve with Port Relief

Operating Mass

FRONT UNLADEN :	4400 kg
REAR UNLADEN :	1640 kg
TOTAL UNLADEN :	6040 kg
LIFTING CAPACITY :	1350 kg

Wheel Drive System

WHEEL MOTOR :	Poclain MSE18 2800cc
WHEEL TORQUE :	13300 NM per Wheel

Cabin Standard

TYPE :	Frame integrated. Full driver protection with guarded side doors and front windscreen
SEAT BELT :	Suspended Lap Belt; 4 Point Harness Optional

Cabin Air Conditioned

TYPE :	Frame Intergrated, Sealed and Pressurised
HVAC SYSTEM :	12V Fan, Engine Belt Driven Air Con Compressor
SEAT BELT :	Suspended Lap Belt; 4 Point Harness Optional
WINDOWS :	Glazed Windscreen With Wiper, Glazed Operator Door Windows
PROTECTION :	HD Removable Windscreen Guard; Removable Operator Door Window Guards

